# QuantaMesh BMS T1048-LY4R





- ONIE Pre-loaded
- x86 Support
- ONL Ready
- BMC Built-in



Data center networks face changes with hardware and meeting the requirements of the software it hosts. Quanta Cloud Technology provides a series of Bare Metal Switches, the QuantaMesh BMS product line, that addresses these changes in the data center market. The QuantaMesh BMS product lines support speeds up to 100G speeds on their Ethernet Switches. To meet the requirements of high performance, high availability, fast scale out, low latency performance, and continuous serviceability in data center applications, the QuantaMesh BMS product line is the best choice.

BMC (Baseboard Management Controller) embedded on the server as the core of the Intelligent Platform Management Interface (IPMI) architecture can now be implemented in the Ethernet switch. In addition to providing health monitoring of the temperature, power status, and cooling fans; BMC also aids in the deployment and management of software and hardware peripherals.

QuantaMesh T1048-LY4R supports 48 10BASE-T/100BASE-TX/1000 BASE-T and 4 1/10G SFP+ ports equipped with BMC in a compact rack unit size. T1048-LY4R plays a management role in a server rack with not only Ethernet switch functions but also IPMI 2.0 compliance. With ONIE (Open Network Installation Environment) pre-loaded it can be used with any OS which supports the ONIE installer to achieve agile installation and fast response for today's IT demands.

# **About OCT**

Quanta Cloud Technology (QCT) is a global data center solution provider. We combine the efficiency of hyperscale hardware with infrastructure software from a diversity of industry leaders to solve next-generation data center design and operation challenges. QCT serves cloud service providers, telecoms and enterprises running public, hybrid and private clouds.

Product lines include hyper-converged and software-defined data center solutions as well as servers, storage, switches, integrated racks with a diverse ecosystem of hardware component and software partners. QCT designs, manufactures, integrates and services cutting edge offerings via its own global network. The parent of QCT is Quanta Computer, Inc., a Fortune Global 500 corporation.







# Found at: www.QCT.io/wheretobuy

**United States** 

QCT LLC., Silicon Valley office 1010 Rincon Circle, San Jose, CA 95131 TOLL-FREE: 1-855-QCT-MUST TEL: +1-510-270-6111 FAX: +1-510-270-6161 Support: +1-510-270-6216

China

云达科技,北京办公室 (Quanta Cloud Technology) 北京市朝阳区东大桥路12号润诚中心2号楼 TEL: +86-10-5920-7600 FAX: +86-10-5981-7958

云达科技,杭州办公室 (Quanta Cloud Technology) 浙江省杭州市西湖区古墩路浙商财富中心 4 号楼 303 室

TEL: +86-571-2819-8650

Japan

Quanta Cloud Technology Japan 株式会社 日本国東京都港区芝大門二丁目五番八号 牧田ビル 3階

TEL: +81-3-5777-0818 FAX: +81-3-5777-0819

Taiwar

程 電 達 科技 (Quanta Cloud Technology) 桃園市龜山區文化二路 211 號 1 樓 TEL: +886-3-286-0707

FAX: +886-3-327-0001

Germany

Quanta Cloud Technology Germany GmbH Hamborner Str. 55, 40472 Düsseldorf TEL: +49-2405-4083-1300

Other regions

Quanta Cloud Technology No. 211 Wenhua 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan

TEL: +886-3-327-2345 FAX: +886-3-397-4770

QCT authorized partner

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their respective holders. Copyright © 2014-2017 Quanta Computer Inc. All rights reserved.

# **Physical ports**

- Port configuration: 48 10/100/1000BAE-T and 4 1/10GbE SFP+ ports
- · Management Port:

Out-of-band management port:

1 x RJ-45 (10/100/1000BASE-T)

1 x SFP (1000BASE-X)

· Console Port: 1 (RJ-45)

· **USB:** USB 2.0

## **Performance**

· Switching capacity: 176Gbps

· Maximum forwarding rate: 131Mpps

• **MAC:** 16K

# **High Availability**

· Redundant power supply: 1+1

· Hot-swappable fan tray: 3 fixed fans

#### **BMC**

- · IPMI: v1.5/v2.0 compliance
- · Serial over LAN
- · SNMP: v1/v2/v3
- · SMASH
- · HTTPS
- · Health status and hardware monitoring
- · Event log
- · PEF and PET
- · Chassis management
- · Watchdog and system re-start

## **Mechanical**

· Dimension (HxWxD): 43.2x440x394mm

• Weight: T1048-LY4R 1 + 1 PSU: 6.04kg(NET)

T1048-LY4R Single PSU: 5.57kg (NET)

# **Environmental Specifications**

· Operating temperature: 0~45°C

· Operating humidity: 90% maximum relative humidity

# **Electrical**

· Power requirement: 100~240VAC, 50/60Hz

· Power consumption: 66 watts (100% fan duty)

· Safety: UL, cUL, CB

• EMC: CE, FCC

# **Supported Optics and Cables**

- · 1000BASE-T: Cat 5e and Cat 6A (100m/330 ft)
- DAC cable (SFP+): 0.5m, 1m, 1.5m, 2m, 2.5m, 3m, and 5m
- · AOC cable (SFP+, 850nm, MMF): 1m, 3m, 7m, 10m, 20m, and 100m
- $\cdot$  10G optic (SFP+, LC, 850nm, MMF): <code>10GBASE-SR</code> optic
- · 10G optic (SFP+, LC, 1310nm, SMF): 10GBASE-LR optic

# **Order Information**

- · BMS T1048-LY4R (1LY4BZZ0STA) (Front to Back, 1+1 PSU, rail kit included)
- · BMS T1048-LY4R(1LY4BZZ0STB) (Back to Front, 1+1 PSU, rail kit included)
- $\cdot$  BMS T1048-LY4R (1LY4BZZ0STE) (Front to Back, single PSU, rail kit included)
- · BMS T1048-LY4R(1LY4BZZ0STF) (Back to Front, single PSU, rail kit included)
- · BMS T1048-LY4R (1LY4BZZ0STG)

(Front to Back, 1+1 PSU, rail kit included, Rangeley with CL OS pre-loaded, US only)

· BMS T1048-LY4R(1LY4BZZ0STH)

(Back to Front, 1+1 PSU, rail kit included, Rangeley with CL OS pre-loaded, US only)

· BMS T1048-LY4R (1LY4BZZ0STI)

(Front to Back, single PSU, rail kit included, Rangeley with CL OS pre-loaded, US only)

· BMS T1048-LY4R(1LY4BZZ0STJ)

(Back to Front, single PSU, rail kit included, Rangeley with CL OS pre-loaded, US only)



Intel Inside®. New Possibilities Outside.

Intel, the Intel logo, Intel Inside, Intel Inside logo, Intel Atom and Intel Atom Inside are trademarks of Intel Corporation in the U.S. and/or other countries.